HAPPY BUCCANEER



HAPPY S-TYPE
HAPPY BUCCANEER
HAPPY D-TYPE
HAPPY R-TYPE
TRA-TYPE




Happy Buccaneer has been one of a kind since she came into operation. She has set the industry standard for a long time. With her 2 x 700 mt Huisman crane capacity, 1400 mt combined, and her large stability she is able to utilize her full crane capacity in outreach and lifting height. The latter is still unrivalled today in the worldwide heavy lift fleet. Happy Buccaneer also offers ro-ro capacity up to 2500 mt by using the ramp and the tween deck.

Like most of the vessels of the BigLift fleet Happy Buccaneer is able to lift cargo up to full combined crane capacity without using a stability pontoon. This greatly increases safety and reliability of such critical operations.

With an impressive track record in heavy lift and special projects as offshore modules, cranes, turrets and power plant parts Happy Buccaneer has proven herself many times during the installation of the biggest ship unloaders and wharf decks around the Australian waters.


Supported by BigLift's in house engineering and operations department Happy Buccaneer is still extending her capabilities while maintaining the high level of safety and reliability required.

HAPPY BUCCANEER





HAPPY BUCCANEER





HAPPY BUCCANEER

01	100 7400 44 7440 4140				
Class	LRS № 100 A1 № LMC UMS				
Principal Dimensions	Length overall Length p.p. Breadth moulded Breadth extreme Summer draft Draft "open sailing"		145.89 134.00 28.30 28.43 8.24 7.02	m m m m	
Deadweight	Summer (sea water)		13,740	mton	
Tonnage	Inte GT NT	ernational 16,341 4,902	Panama 16,352 13,473		Suez 16,081 12,642
Capacity	Lowerhold Tween deck		7,517 12,391		
Floor space	Weather deck Tween deck Tank top		3,067 2,275 1,344	m^2	
Hatch openings	Weather deck Tween deck		110.5 x 20.6 67.0 x 20.0		
Heights	Tween deck Lower hold Total hold		5.38 5.42 12.25	m	
Allowable loads	Weather deck hatch cover with pillars Tween deck hatch covers with pillars Tank top	S	15.0 5.0 15.0	t/m ² t/m ² t/m ² t/m ²	
Cranes	Combinable Situated on starboard side Fitted with trolley		1,400 2 x 700 2 x 25	mt	SWL SWL SWL
Ramp	Position Dimensions Capacity Working height		stern 20.3 x 7.6 2,500 2 - 3.5	mt	
Main engine	2 x Hitachi Sulzer 6ZAL 40 Bowthruster Service speed		2 x 3,840 760 14.75	kW	at draft 6.00 m
Container capacity			1,050	TEU	

HAPPY BUCCANEER

Happy Buccaneer Amsterdam The Netherlands 1984

These particulars are believed to be correct, but without guarantee, and they must not be used as basis for Charter Parties or contracts without Owners' explicit written authority.





